



Variable Rate 47H  
Photo with Options

# 47H Heavy Duty Tandem Spreader

## Specifications:

- Capacity - 233 cubic foot, max load 10 tons
- Hull - 10' x 102", 304 stainless, bolt-on
- All stainless hull, gate, dishes, blades, conveyor
- Fertilizer and lime
- Conveyor - clinched, 24" or 16"
- Heavy duty 24" dishes (3/16"), 6 Blades (1/4")
- Trailer main frame - 2 x 6 tubing, powder coated paint, blue
- Lift - 4 x 6 tubing
- Hub - 10 bolt, mounted on 1/2" heavy round tubing
- Axle - tandem, heavy duty slipper springs, 6 leaves
- Tires - 19L x 16.1, 12 ply
- Hitch - cat 3, clevis/pintel combination
- Tractor hydraulic four hose system - open/closed
- Drive: ground drive wheel or hydraulic motor
- Hydraulic valve - NCI exclusive for easy, clean operation
- Inverted "vee"
- Standard or variable rate controllers available

## Options:

- Window
- Herculiner
- Tarp
- Spinner speed monitor - NCI with 409 stainless star
- Many others



Ground Drive  
with Third Rate



The Spreader of Choice

800.241.1350  
www.newtoncrouch.com  
sales@newtoncrouch.com

## Spreading Innovation Since 1940



Newton Crouch Inc has been a leader in the Ag industry since 1940. Growers and operators repeatedly choose NCI spreaders for their operations. Spread-Tek™ design, a NCI exclusive, allows our spreaders to lay out the flattest, most uniform, most consistent spread pattern in the industry, with a six blade dish. Operators agree that Newton Crouch spreaders are the easiest to set up and adjust for the most desirable spread pattern.

### The **BEST** Spreader You Can Buy

Proven advantages on most Newton Crouch Spreaders:

- Accurate spread pattern
- Wider spread pattern
- Spread-Tek™ Application
- Increased crop production
- Stress proof spindles
- 24 in conveyor chain - widest in industry
- Bolt on frame for easy maintenance
- Proprietary hydraulic valve to reduce maintenance cost
- Increased clearance to row
- Dependable, friendly service
- Easiest to load and operate
- Tube frame that fully supports hull
- Tubing trailer frame, no ledges for product to accumulate
- Steeper side panels for less bridging with lime and gypsum
- 304 stainless dishes
- Bolt in gate with stainless jack
- Heavier overall construction and reinforced frame
- Grease-able spinner motors
- Triple sealed spinner motors mounted under dishes to protect from elements
- Official spreader of the Sunbelt Expo
- Low cost of ownership



49H102RAVX-24F Turf



45500JBDW



47NC102TH-24

**Full Product Line  
to Meet Your  
Application Needs**

[www.newtoncrouch.com](http://www.newtoncrouch.com)  
[sales@newtoncrouch.com](mailto:sales@newtoncrouch.com)  
1.800.241.1350

